

TECHNICAL SPECIFICATIONS

WEIGHT (TONNES)	CLASS	WIDTH (IN)	CAPACITY (VC)	WEIGHT (LB) ¹
1.5 – 2.2	15	24	0.10	100
		30	0.10	110
2.3 – 3.9	35	36	0.22	230
		42	0.26	260
4.0 – 5.9	50	42	0.33	360
		48	0.45	380
6.0 – 9.9	75	36	0.50	350
		42	0.60	400
		48	0.70	490
		60	0.84	555
10 – 15	120	60	1.00	890
		66	1.12	970
		72	1.25	1 050

WEIGHT (TONNES)	CLASS	WIDTH (IN)	CAPACITY (VC)	WEIGHT (LB) ¹
16 – 19	160	60	1.50	1 050
		66	1.37	1 080
		72	1.50	1 120
20 – 23	200	60	1.50	1 380
		66	1.75	1 450
		72	2.00	1 570
		78	2.25	1 950
		72	2.00	1 820
24 – 29	270	78	2.25	1 920
		84	2.50	2 028
30 – 39	300	72	2.50	2 600
		78	2.75	2 730
		78	3.50	3 150
		84	3.00	3 200

WEIGHT (TONNES)	CLASS	WIDTH (IN)	CAPACITY (VC)	WEIGHT (LB) ¹
		84	3.50	3 530
		78	3.25	3 200
		78	3.75	3 425
40 – 49	400	84	3.50	3 450
		84	4.00	3 580
		96	4.00	3 980

** Other models and sizes available on request.*

(1) The weights quoted do not include the female coupler.