EnviroKleen®: Frequently Asked Questions

What is EnviroKleen?

EnviroKleen is a patented Synthetic Organic Dust Control[®]; a synthetic organic fluid formulated with a polymeric binder system that works to agglomerate fine silt or clay particles making them larger so they cannot become airborne. It is applied topically without a requirement for addition of water. The advantage is that it is long lasting and is not destroyed by mechanical damage to the surface by heavy or tracked vehicles. EnviroKleen works by ballasting and agglomerating small particles, providing binding and densification of the surface. The natural penetration and action of the traffic 'work' the EnviroKleen into the surface.

Is EnviroKleen safe for the environment, personnel and equipment?

YES ---- it is a safe, colorless, odorless, highly refined fluid. When used as directed, EnviroKleen has no adverse health effects to people or equipment. Beyond normal hygiene, no special precautions are required. EnviroKleen is approved by the U.S. EPA Environmental Technology Verification Program. It is not a controlled substance under OSHA or WHMIS and has no exposure limits. Extensive acute and chronic toxicity testing data conclusively shows that it does not induce a toxic reaction when it is exposed to skin, eyes or lungs. It is also biodegradable and rigorous quality assurance control at every stage of the manufacturing process ensures the consistency of EnviroKleen.

Are all Synthetic Fluids the same?

All synthetic fluids are not the same. Midwest through extensive research and development invented the patented product category Synthetic Organic Dust Control. 'Synthetic' as used in Synthetic Organic Dust Control relates to impact on the environment and is a US EPA definition. The requirements to be 'synthetic' established by the US EPA are based on the environmental tests that a product must meet for sediment toxicity, biodegradability, PAH content, aquatic toxicity and being oil sheen free. Synthetic Organic Dust Control is defined by environmental requirements; synthetic fluid is defined by motor oil requirements. Synthetic fluid is the American Petroleum Institute's (API) requirement for base oil that will be used in motor oils. This API meaning of 'synthetic' has importance to Castrol, Valvoline, Mobil and Quaker State and the performance of their brand name motor oils. The API criteria do not contain environmental meaning. Because of the success of EnviroKleen, EK35°, Diamond Doctor°, and Arena Rx°, attempted knockoffs are starting to make synthetic fluid claims. Analysis of some of these products indicates they do not provide the same chemistry and binding properties.

What is EnviroKleen used for?

EnviroKleen is applied to unpaved roads; haul roads, helicopter landing zones, tank trails, parking lots and unpaved open areas (concert venues, ball diamonds, construction sites, etc.) for environmentally safe dust control. It is particularly well suited for environmentally sensitive areas and areas where maintaining natural aesthetics is a priority.

How does EnviroKleen work?

EnviroKleen is applied and given approximately two weeks to coat and impregnate every soil or aggregate particle. However, you are able to use the area immediately. As the soil or aggregate is conditioned with EnviroKleen, you will notice a dark, almost wet look that exists immediately upon application will, over a period of week change to a lighter, dryer look. It is in this process of visible change that you know the EnviroKleen is working its way through and into all of the particles. The EnviroKleen approach to controlling dust is consistent with sound soil and aggregate principles. The binder system in EnviroKleen interlocks and binds loose soil and aggregate with a combination of adhesive and cohesive mechanisms. These systems capture fines as they are generated by traffic and wheel friction and keep them in the surface, preventing them from escaping as dust. The binders also prevent particles from moving apart, leaving open space for water to occupy.

How much EnviroKleen will I need?

A Midwest representative can answer that question by taking into consideration the area you need treated, type of traffic, type of soil and site specific needs for dust control and stabilization. Call 1-800-321-0699 or (330) 456-3121 to find out.



EnviroKleen®: Frequently Asked Questions

How do I apply EnviroKleen?

There are many equipment options available for application of EnviroKleen. Hydroseeding systems, either trailer mounted or skid mounted (multi-functional with spray bars, hose reels, and tower guns), scraper mounted water distribution systems, water trucks, and asphalt spreaders will also work well. Centrifugal pumps work best and require less maintenance. Because EnviroKleen is applied neat (without addition of water) metered spray trucks with appropriate sized spray nozzles are required for application. Watering trucks are designed to apply much larger volumes of product and would require modification to apply EnviroKleen.

Midwest has developed the E-Sprayer[™] System which provides rapid and efficient application of dust suppressant chemicals via a spray bar or fire hose. This unit is selfcontained and very effective. Midwest also offers complete Turnkey Delivery and Application Services and Dust Control Service Programs.

What personnel would be required to spray EnviroKleen and is there any special training required?

Midwest can provide all support necessary for application including our personnel operating in secure environments with you. We are also available for engineering support and training as required.

Do I need to add water to dilute EnviroKleen before applying?

EnviroKleen DOES NOT need to be diluted with water. It is not water soluble. It is applied neat.

Will I still need to use water?

NO. EnviroKleen eliminates the need to use water.

How do I clean EnviroKleen out of my equipment after application / use?

Drain lines, pumps and tanks of EnviroKleen after use. Our Synthetic Organic Dust Control products are non-corrosive and non-binding to equipment so no special cleaning is required. Dawn dish soap works best.

Midwest Industrial Supply, Inc.Tel 31101 3rd Street SoutheastFaxCanton Ohio 44707Tollwww.midwestind.comF817 © 2017 Midwest Industrial Supply, Inc.

Tel 330.456.3121 Fax 330.456.3247 Toll Free 1.800.321.0699

Will EnviroKleen freeze during cold, winter weather?

No. EnviroKleen will not freeze even at -40 degrees F. Therefore it is ideal in cold climates where there exist concerns of temperatures affecting the ability to have dust control.

Will EnviroKleen burn the grass in surrounding areas?

No, generally it will not burn grass. However, if a large amount of EnviroKleen has saturated a grassy area rinsing with water and a small amount of Dawn dish soap is suggested. Otherwise, the EnviroKleen may act to intensify the sun much as tanning oil does.

How are your products packaged and shipped?

5 gallon (20 liters) Plastic Pails 55 gallon (208 liters) Plastic Drums 275 gallon (1,050 liters) Refillable Steel-Caged Plastic Totes 5,000 gallon (18,925) Bulk Tanker Truck Loads (U.S. and Canada Deliveries Only) 5,000 gallon (18,925 liters) IMO/ISO Tank Containers 20,000 gallon (75,700 liters) Railcar (U.S. and Canada Deliveries Only)

Shipping Methods:

Shipped FOB (Freight on Board) Canton, Ohio

Carriers Used:

UPS, Common Carriers (i.e. - R+L Carriers, Ward Trucking, Estes Express Lines, etc.), Midwest's Own Bulk Truck Load Fleet

How soon will my order be shipped?

Orders are fulfilled and shipped within 24-48 hours upon receipt.

